

HIGH DUMP CART

9016-HD



Art's Way
ART'S WAY

artsway.com

Our “big dump cart” is as big as they get. In fact, with a capacity of 40,000 lb. it’s ready for mammoth loads. For comparison, our nearest competitor only has a capacity of 30,000 lb. And with the frame on the outside, there’s no “ribcage” on the inside to trap materials. The result is a reliable, versatile, high-performing powerhouse of dumping.

Ideal for wet fields, the rugged understructure rolls through tough conditions. Pull it alongside a harvester when opening and dump when full. This allows the harvester to run at a much more continuous pace, greatly reducing the amount of time lost.



Impressive capacities

The 16-ft. box length has a capacity struck of 930 cu. ft. and a rated load capacity of 40,000 lb.

- ▶ Reversible hitch for left- or right-side dump
- ▶ Axles adjust fore and aft for best weight distribution
- ▶ Massive 4.5 in. bolt-in cold rolled spindles with heavy duty 10 bolt hubs with studs and nuts
- ▶ 30.5L – 32 16-ply bias tires
- ▶ Swivel hitch clevis adjustable up and down
- ▶ A 12,000 lb. crank-style jack
- ▶ Optional weigh scale system

Primary/secondary cylinder elevator raises loads evenly

9016-HD features primary and secondary cylinders to raise their loads uniformly without need for straightening cables and pulleys. With this system, the large 5 in. primary and 4 in. secondary cylinders require less oil.



Wide Tires



Massive undercarriage



Left- or right-hand dump

2-Wheel Flotation Tires Reduces Downtime

Smooth movement through muddy field conditions are a breeze with flotation tires reducing compaction and furrows.

Wide Stance Stability

The high dump cart has a massive undercarriage, a wide stance and counterweight for maximum stability.

Easily converts to left- or right-hand dump

A reversible hitch makes it easy to change from right-hand to left-hand dump as needed to accommodate harvester movement. The heavy-duty, height-adjustable, pivoting 2 in. bull-pull hitch and three-position telescoping tongue provide stable and smooth transport.

Rugged all-steel construction

Four large greasable hinges (box to elevator) for added strength



9016-HD HIGH DUMP CART

9016-HD High Dump Cart	
Length of box	16 ft.
Capacity struck	930 cu. ft.
Rated load capacity	40,000 lb.
Lip clearance	7-13 ft.
Pivot height	9-15 ft.
Axle clearance	20 in.
Height (low side)	11 ft.
Height (high side)	12 ft. 6 in.
Tread width (centers)	37 in.
Lift cylinders	5 in. and 4 in. primary secondary
Tilt cylinders	5 in. parallel
Recommended min. flow	15 gmp
Dump cycle time @ 15 gpm	Approx. 90 seconds
Dump cycle time @ 20 gpm	Approx. 20 seconds
Tongue weight %	8-11%
Sideways reach	Lowest height > 16 in. Highest height > 42 in. (outside edge of tire to lip)
Dump	Right- or left-hand
Axle placement	4 positions
Wheels	10 bolt
Spindles	4-1/2 inch bolt-in cold rolled
Tires	30.5L-32 16 ply flotation
Hitch	Swivel (adjusts up and down)
Jack	12,000 lb. 2-speed crank
Scale system	Optional weighbar package with Digistar 640XL indicator

Art said it best: "When it's time to take a major dump, do it quick and get back to work."

Art's Way: How Work Gets Done.



Want to watch it work?
See the high dump cart in action by scanning the QR code below.



Get your hard work done with Art's Way – contact your nearest dealer today.

(712) 208-8467 | artsway.com



Art's Way Manufacturing Co. Inc. reserves the right to change design or specific application purposes. Photographs contained herein may be displayed with safety shields and/or guards removed to show mechanical functions only. All brand or product names are or may be trademarks of, and are used to identify products and services of their respective owners or its subsidiaries and divisions in the U.S. and/or other countries. All specifications are subject to change without notice. © 2022 Art's Way. All Rights Reserved.

